



TOYOTA 32-8FD30 - 4.5m CONTAINER MAST DIESEL

CAPACITY: 3000 kg @ 500 mm LOAD CENTER

SPECIFICATIONS

Manufacturer	Toyota
Model	32-8FG30
Load Capacity free lift	3000 kg
Load Capacity @ 4.5m	3000 kg
Load Center	500 mm
Power Type	Diesel
Operator Position	Rider Seated
Tyre Type (Front/Rear)	Pneumatic
Wheels (Front/Rear)	2x / 2
Maximum Fork Height (MFH)	4,500 mm
Free Lift	135 mm
Fork Size (T x W x L)	42 x 120 x 1070 mm
Fork Spread (MAX / MIN)	1020 mm / 240 mm
Tilt Range (FWD / BWD)	6° / 11°
Length to Fork Face	2,775 mm
Overall Width	1,240 mm
Mast Lowered Height	2215 mm
Mast Extended Height	5315 mm
Overhead Guard Height	2,170 mm
Turning Radius (Outside)	2,430 mm
Load Distance	485 mm
Rear Overhang	595 mm
Right Angle Aisle Width	2,915 mm
Travel Speed Full Load (FWD/REV)	18.5 km/h
Travel Speed No Load (FWD/REV)	19 km/h
Lift Speed Full Load	510 mm/sec
Lift Speed No Load	550 mm/sec
Lower Speed Full Load	500 mm/sec
Lower Speed No Load	500 mm/sec
Max Drawbar Pull Full Load	18,000 N (1,890 kg)
Max Drawbar Pull No Load	10,300 N (640 kg)
Drawbar Pull @1.5km/h Full Load	17000 N (1,730 kg)
Max Gradeability Full Load	22%
Max Gradeability No Load	25%
Gradeability @1.5 km/h No Load	20%
Total Weight	4190kgs
Weight Distribution Full Load Front	5610kgs
Weight Distribution Full Load Rear	980kgs
Weight Distribution No Load Front	1470kgs
Weight Distribution No Load Rear	2720lgs
Tires Front	28x9-15-12PR
Tires Rear	6.5-10-10PR

